

## Tar Remover

### Description

Highly effective solvent combination to remove sap and tar spots on automobiles, campers, motorcycles, bicycles, tools, etc. Tuned for high efficiency and paint compatibility.

### Properties

- highly effective
- outstanding compatibility with paint
- increases shine
- dissolves resin and tar-type residues
- removes tar spots

### Technical data

|                    |   |
|--------------------|---|
| Propellant         | Propan, Butan / propane, butane         |
| Viscosity          | n.a.                                    |
| Color / appearance | farblos / colourless                    |
| Base               | teeraktive Lösungsmittel / tar solvents |
| Density at 20 °C   | 0,66 g/ml                               |
| Flash point        | -60 °C                                  |

### Areas of application

For cleaning tar soil on all kinds of vehicles, e.g., for removing tar, asphalt, grease stains and fresh paint stains. Do not use on polycarbonate plastics and acryl glass.

### Application

Spray Tar Remover onto the places to be cleaned and leave to act for a short while. Wipe off with a cloth or sponge.



### Available pack sizes

|                    |                    |
|--------------------|--------------------|
| 400 ml Can aerosol | 1600<br>D-GB-I-E-P |
| 400 ml Can aerosol | 7603<br>D-RUS-UA   |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**