

# Product information

## Motorbike MoS2 Shooter

PI 19/03/03/2020



### Description

Reduces friction and wear, thus reducing oil and fuel consumption. Increases engine's running smoothness and leads to fewer malfunctions.

### Properties

- minimizes friction
- reduces wear
- smooth engine running
- reduces oil and fuel consumption
- increases smooth operation
- prevents operational malfunctions
- miscible with all commercially available gear oils
- miscible with all commercially available motor oils
- tested for the use with catalytic converters

### Technical data

Base	MoS2-Mineralöl / MoS2 mineral oil
Color / appearance	schwarz / black
Density at 20 °C	0,903 g/ml DIN 51757
Particle fineness of MoS2	0,3 µm
Viscosity at 40 °C	95 mm <sup>2</sup> /s
Flash point	201 °C

### Areas of application

Suitable for all 2-stroke and 4-stroke engines. 20 ml (1 tube) sufficient for 1 l of motor oil. 2-stroke engines: 10 ml per 10 l of fuel mixture or 20 ml for 400 ml of 2-stroke oil. Tested on engines with catalytic converters.

### Application

In 4-stroke engines at each oil change; in 2-stroke engines, add when filling the oil/fuel tank. Shake well before use! **Dosage:** In 4-stroke engines or the transmission: 20 ml (1 tube) is sufficient for 1 l of motor oil. In 2-stroke engines (mixture lubrication): 10 ml per 10 l of fuel mixture or 20 ml for 400 ml of 2-stroke oil with separate lubrication.



### Available pack sizes

20 ml Tube plastic	3444 GB
20 ml Tube plastic	20561 E
20 ml Tube plastic	20563 F
20 ml Tube plastic	20574 TR
20 ml Tube plastic	20575 VN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**