

Pro-Line PTFE High Performance Lube Spray



Description

Synthetic high-performance lubricant with PTFE for a wide range of applications. The high pressure and temperature resistances as well as the excellent water resistance help to ensure a lasting lubricant film. The solid lubricant ensures very good damping and emergency running characteristics. Extremely adherent and penetrative.

Properties

- universal application
- excellent adhesion
- outstanding corrosion protection
- broad operating temperature range
- suppresses noise and vibration
- good water resistance
- has a lasting effect
- highest load-carrying capacity

Available pack sizes

400 ml Can aerosol 20612
GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

Color / appearance	weiss-gelb / white-yellow
Base	Syntheseöl, PTFE / synthetic oil, PTFE
Propellant	Propan, Butan / Propane, Butane
Operating temperature range	-30 bis / to +180 - kurzfristig bis / intermittent to + 200 °C

Areas of application

Universally used in the car sector as well as by craftsmen. For lubricating with tight tolerances and eliminating popping and creaking of hinges, joints, rods, steering levers and door retaining straps, etc.

Application

Spray an appropriate amount onto the cleaned parts that have to be treated. Even greater penetrative effectiveness can be obtained by reducing the spraying distance.

Comment

Follow the relevant instructions of the vehicle manufacturer.