

Top Tec 6200 0W-20



Description

High-tech low-friction motor oil based on synthetic technology. Developed for the high requirements of Audi, Porsche and VW. The lower viscosity of the Longlife IV lubricant ensures excellent cold-start behavior and improves the efficiency of the engine. Offers an additional reduction of approx. 1.5 % in consumption compared with the already fuel-saving Longlife III. The innovative additive technology guarantees excellent protection against wear, impressive engine cleanliness and greater oxidation stability. Enables extremely long oil change intervals (WIV etc.).

Properties

- excellent cold-start behavior
- excellent wear resistance
- highest fuel economy
- shortens the start time
- outstanding resistance to oxidation
- optimum protection when using E10 fuel
- increases operational reliability
- tested for turbochargers and catalytic converters

Specifications and approvals:

VW 508 00 • VW 509 00

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Porsche C20

Technical data

Viscosity SAE class	0W-20 SAE J300
Density at 15 °C	0,835 g/cm ³ DIN 51757
Viscosity at 40 °C	39,6 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,1 mm ² /s ASTM D 7042-04
Viscosity at -40°C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35°C (CCS)	<= 6200 mPas ASTM D 5293
Viscosity index	184 DIN ISO 2909
HTHS at 150°C	>= 2,6 mPas ASTM D 5481
Pour point	-60 °C DIN ISO 3016

Technical data

Evaporation loss (Noack)	10,3 % CEC-L-40-A-93
Total base number	8,1 mg KOH/g DIN ISO 3771
Flash point	230 °C DIN ISO 2592
Color / appearance	grün

Areas of application

Specially developed for the requirements of various vehicle models of Audi, Porsche and VW. The motor oil may only be used in gasoline and diesel engines with a particulate filter (such as e.g. TFSI, TDI) that require a lubricant of VW standard 508 00/509 00. Not backwards compatible.

Application

Note the vehicle and engine manufacturers' operating instructions.

Available pack sizes

1 l Canister plastic	20787 BOOKLET
4 l Canister plastic	20788 BOOKLET
5 l Canister plastic	20789 BOOKLET
20 l Canister plastic	20782 D-GB-I-E-P
60 l Drum sheet metal	20783 D-GB
205 l Drum sheet metal	20785 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.