Product information

Pro-Line Engine Flush



Description

The highly effective detergent and dispersant additives in association with the carrier fluid have been tested in the laboratory and in practical field trials for their ability to dissolve sludge and lacquer formers. All types of oil-soluble and oil-insoluble residues are brought into suspension and removed during the following oil change. An engine, which has been cleaned of deposits and contamination and is then filled with fresh oil that is not contaminated with old impurities can develop its full performance characteristics.

Properties

- highly economical
- gentle cleaning
- suitable for diesel particulate filters
- tested for turbochargers and catalytic converters
- simple to use
- no pollution to the environment
- does not attack common sealing materials
- rapid cleaning

Technical data

Color / appearance gelb, braun / yellow,

brown

Base Additiv, Trägerflüssigkeit

/ additive, carrier liquid

Density at 20 °C 0,81 g/cm³

DIN 51 757

Flash point 63 °C

DIN ISO 2592

Pour point -45 °C

DIN ISO 3016

Form flüssig / liquid

Viscosity at 40 °C <7 mm²/s

Odor charakteristisch / characteristic

Areas of application

Cleaning and flushing out the oil systems of gasoline and diesel engines. Improves hydraulic function e.g. VVT, VANOS and other oil actuated switches and valves. Can be safely used in vehicles with timing belt running in oil.

Application

One 500 ml can is sufficient for up to 5 litres of oil. Add Pro-Line Engine Flush to the engine oil at running temperature before changing the oil. After adding the product, allow the engine to idle for approx. 10 to 15 minutes depending on the degree of



contamination. Then change the oil and the filter. Pro-Line Engine Flush is compatible with all commercially available engine oils. **Note: Not suitable for use on motorbikes with wet clutches.**

Available pack sizes

500 ml Can sheet metal 2427

D-GB-I-E-P

500 ml Can sheet metal 2978

GB-DK-FIN-N-S

500 ml Can sheet metal 2662

D-PL-BG

500 ml Can sheet metal 20810

D-GB-SLO-SRB-HR

500 ml Can sheet metal 20684

D-GB-CN

1 l Can sheet metal

2425 D-GB-I-E-P

5 l Canister plastic 2428

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.