

Fuel Protect

Description

Fuel Protect is an ash-free, self-mixing combination of active agents, formulated according to the latest additive, fuel and engine technologies and specially developed to fulfill the demands of today's engines, fuels and running conditions.

Properties

- good corrosion protection
- binds and removes water
- prevents carburetor icing
- environmentally friendly
- tested for turbochargers and catalytic converters
- economical

Technical data

Base	Additive, spezielle Trägerflüssigkeit / additives, special carrier fluid
Color / appearance	hell, farblos / pale, colorless
Density at 15 °C	0,799 g/ml
Refractive index at 20 °C	1,382
Form	flüssig / liquid
Viscosity at 40 °C	<7 mm ² /s
Odor	charakteristisch / characteristic

Areas of application

For all gasoline engines (carburetor and fuel-injection engines). For rectifying difficulties with starting, irregular idling, poor throttle response, performance losses. Prevents the problem of corrosion in the gasoline system and thus prevents operational malfunctions.

Application

Add to fuel whenever filling up. One 300 ml can of Fuel Protect is sufficient for 60 liters of fuel.



Available pack sizes

300 ml Can sheet metal	2530 GB-ARAB-F
300 ml Can sheet metal	2811 DK/N-S-FIN
300 ml Can sheet metal	2955 GB-GR-I
300 ml Can sheet metal	8356 D-E-P
300 ml Can sheet metal	3964 D-RUS-UA
5 l Canister plastic	2855 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.