

# Product information

## Motorbike Radiator Stop Leak

PI 26/26/02/2020



### Description

Dispersion for sealing leaks in coolant circuits. The product reliably seals hairline cracks and small leaks. Can be used preventively when repair work has been carried out on the cooling system. The solids dispersion is stabilized in carrier fluid.

### Properties

- compatible with conventional coolant water refiners and antifreezes
- permanently and reliably seals hairline cracks and small leaks
- no harmful side effects
- suitable for aluminum radiators

### Technical data

Form	flüssig / liquid
Color / appearance	je nach Spezifikation / according to specification
Density at 20 °C	1,05 g/cm <sup>3</sup>
Solubility in water	mischbar / mixable
Odor	schwach / weak
Flash point	>100 °C
Viscosity at 40 °C	130 mm <sup>2</sup> /s

### Areas of application

For sealing minor leaks in coolant systems with and without coolant filter. Also suitable for aluminium and plastic radiators.

### Application

Shake well before use. Add contents to the cold cooling system. Then drive the vehicle for at least 10 minutes. Contents will treat up to 5 liters of coolant.

### Comment

Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).



### Available pack sizes

125 ml Can sheet metal	3043
	D-GB-E
125 ml Can sheet metal	5924
	D-F-I-GR

**Our information is based on thorough research and may be considered reliable, although not legally binding.**