Product information Brake Anti-Squeal Paste (can with brush)

PI 22/02/08/2018

LIQUI MOLY

Description

Specially developed lubricating and separating paste made from synthetic and ceramic agents. Eliminates squealing noises that occur between brake pistons or contact surfaces and the brake lining.

Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

Technical data

rechnical data	
Form	pastös, flüssig / pastelike,liquid
Color / appearance	blau / blue
Base	synthetische u. keramische Wirkstoffe
Density	1,08 g/ml
Operating temperature range	-40 bis +200 kurzfristig bis +250 / -40 to +200 short term +250 °C als Schmierpaste / as lubricating agent
	-40 bis +1200 / -40 to +1200 °C als Trennpaste / as release agent
Flash point	>210 °C
Odor	schwach / slightly
Shalf life in original coaled	36 months

Shelf life in original sealed 36 months container

Areas of application

For fitting, repair and maintenance work on brake systems. Used for basic lubrication and as a preventive measure against brake squeals. Highly suitable as a universal paste for numerous applications apart from brake systems.

Application

With floating brake calipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After evaporation of the solvents, apply the paste to the cleaned parts at all sliding surfaces, channels and contact surfaces.

LIQUIMOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Comment

Do not apply paste to the friction surface of the lining or the brake disk!

Available pack sizes

200 ml Can aerosol

3074 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

