

Product information

Fluorescent Leak Finder K

PI 14/25/02/2020



Description

Water-soluble leakage fluid for locating water ingress and wind noises quickly and accurately. Fluorescent, ready-to-use mixture with good penetrating properties so that after only a few minutes, the water leak can be located by illuminating the affected area using an indicator lamp (UV flashlight). Rework or complaints following accident repairs or the installation of glass or sliding roofs can thus be avoided.



Properties

- fluorescent
- simple to use
- excellent penetration action
- multifunctional uses
- can be washed off

Available pack sizes

50 ml Can plastic 3339
D-GB

Technical data

Base	Fluoreszenz Farbstoff / fluorescent dye
Color / appearance	hellbrown/ light brown
Odor	charakteristisch / characteristic
Solubility in water	mischbar / mixable
Form	flüssig / liquid
Mixing ratio	1:10 bis 1:500
Density at 20 °C	1,17 g/ml
Shelf life in original sealed container	36 months

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For locating ingress of water after repairs to glass or sliding roofs, accident repairs and for locating wind noises quickly and accurately. Also suitable for locating defective or leaky cooling circuits.

Application

Depending on the application, add to the cooling circuit or dilute with at least 0.5 l of water and use the LIQUI MOLY Pump-spray Bottle (part no. 3316) to spray it onto the entire area in question. After only a few minutes, the water leak can be located by illuminating the affected area using the indicator lamp. Can then be flushed away using clear water.