

## Sealant Remover

### Description

Sealant Remover is a mixture of solvents selected for their fast and thorough cleaning properties.

### Properties

- adheres well to vertical surfaces
- enables work to be performed quickly
- economical
- removes even burnt-on and hardened sealing compounds or adhesives
- dissolves burnt-on, adherent sealant residues

### Technical data

|                    |  |
|--------------------|--|
| Base               | Lösungsmittelgemisch / mixture of solvents |
| Color / appearance | weiß / white                               |
| Propellant         | Kohlenwasserstoff / hydrocarbon            |
| Density            | 0,74 g/ml                                  |
| Flash point        | -60 °C                                     |
| Odor               | charakteristisch / characteristic          |
| Form               | aerosol, flüssig / aerosol, liquid         |

### Areas of application

Can be used for items made of steel, iron and non-ferrous metals, ceramics, wood and glass. Especially suitable for industry and motor vehicles such as valve covers, cylinder heads, water pumps, oil sumps, flange seals and vehicle, engine, exhaust and mechanical parts.

### Application

Shake can vigorously before use. Spray the residues to be removed from a distance of 20-30 cm and leave to take effect for 5-10 minutes.



### Available pack sizes

|                    |              |
|--------------------|--------------|
| 300 ml Can aerosol | 3623         |
|                    | D-GB-I-E-P   |
| 300 ml Can aerosol | 2337         |
|                    | D-DK-FIN-N-S |
| 300 ml Can aerosol | 20882        |
|                    | JP           |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**