

Gear Oil (GL5) 75W-80

Description

GL5 SAE 75W-80 Gear Oil is a high-performance high-pressure gear oil based on synthetic and mineral base oils and high-quality additives. Enables smooth and precise shifting action even in low temperatures. Can also be used to deal with unwanted noise and to solve gear-changing problems.

Properties

- excellent viscosity/temperature properties
- for eliminating shifting problems
- outstanding resistance to oxidation
- outstanding friction characteristics
- outstanding corrosion protection
- very good low-temperature properties
- excellent wear resistance
- optimum stability to aging

Specifications and approvals:

API GL5 • MIL-L 2105 C

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Peugeot Citroen (PSA) B71 2315 • Peugeot Citroen (PSA) B71 2330

Technical data

SAE class (gear oils)	75W-80 SAE J306
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	52,3 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,5 mm ² /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	135 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color number (ASTM)	L2,5 DIN ISO 2049



Areas of application

Specially developed for use in Peugeot and Citroen manual transmissions. Can also be used in other manual transmissions to deal with unwanted noise and to solve gear-changing problems. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Can plastic	3658 D-GB-I-E-P
1 l Can plastic	20463 D-PL-H-RO-TR
20 l Canister plastic	3690 D-GB
20 l Canister plastic	21259 ALGERIEN-GB-ARAB-F

Our information is based on thorough research and may be considered reliable, although not legally binding.