#### LIQUIMOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

#### Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de

# **Product information** Central Hydraulic System Oil 2400

## Description

Central hydraulic system oil 2400 is a specially developed hydraulic oil for PSA group vehicles (Citroen and Peugeot). The combination of selected mineral base oils and high-performance additives enables considerably improved low-temperature characteristics. Excellent operation of assemblies and systems is therefore guaranteed under all operating conditions.

# Properties

- very good low-temperature properties
- high wear resistance
- optimum stability to aging
- outstanding corrosion protection
- excellent viscosity/temperature properties

## Specifications and approvals:

ISO 7308

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

LHM-Plus • Peugeot Citroen (PSA) B71 2710

# **Technical data**

Density at 15 °C	0,865 g/cm³ DIN 51757
Viscosity at 40 °C	20,6 mm²/s ASTM D 7042-04
Viscosity at 100 °C	6,4 mm²/s ASTM D 7042-04
Viscosity at -40 °C	<20000 mPas DIN 51398
Viscosity index	300 DIN ISO 2909
Flash point	120 °C DIN ISO 2592
Pour point	-66 °C DIN ISO 3016
Color / appearance	grün

### Areas of application

For hydraulic systems, e.g. level control, hydraulic brakes, steering systems, etc. in vehicles developed by the PSA Group (Peugeot and Citroen). Central hydraulic oil 2400 can be mixed with older, mineralbased LHM formulations. Commercial vehicles also sometimes require a lubricant with this specification for the lifting equipment of trailing axles and cab tilting equipment. Usage according to the prescribed

specifications from the unit or vehicle manufacturer.

#### Application

The instructions from the unit or automobile manufacturer must be followed. Central hydraulic system oil 2400 can also be used for refilling in systems that are filled with original oil from the manufacturer. Optimum effectiveness, however, is only possible when the product is used on its own (i.e. no mixing).

#### Available pack sizes

1 l Can plastic	3666 D-GB-I-E-P
1 l Can plastic	20979 GB-DK-FIN-N-S

#### Our information is based on thorough research and may be considered reliable, although not legally binding.



PI 13/05/12/2017