

## Top Tec ATF 1800

### Description

Low-viscosity high-performance oil of the new generation for automatic transmissions. It is based on synthesis technology with modern, high-performance additives. Aside from excellent ageing and oxidation stability, optimal shifting is guaranteed under all operating conditions thanks to the extremely high viscosity index. It enables long oil change intervals.

### Properties

- excellent viscosity/temperature properties
- prevents foam formation
- enables a multifaceted range of applications
- stable to oxidation
- outstanding friction characteristics
- high resistance to aging
- very good low-temperature properties
- excellent corrosion protection
- high wear resistance
- outstanding resistance to oxidation

### Specifications and approvals:

Dexron VI • Ford Mercon LV

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Aisin Warner AW-1 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 152 426 • BMW 83 22 0 142 516 • BMW 83 22 2 289 720 • BMW M-1375.4 • Fiat 9.55550-AV5 • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Honda ATF DW-1 • Hyundai SP IV • Mazda ATF FZ • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

### Technical data

Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	28,2 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	5,9 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 10000 mPas ASTM D 2983-09
Viscosity index	161 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	196 °C DIN ISO 2592



### Technical data

Color / appearance	bräunlich/brownish
Color number (ASTM)	L 1,5 DIN ISO 2049

### Areas of application

Developed for ZF 6HP19/26/32 and ZF 8HP 45/55/70/90 type automatic transmissions that are installed in various Audi, BMW, Jaguar, Land Rover, Porsche, etc. vehicles. Meets further specifications, allowing it to cover an even wider range of vehicles.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Can plastic	3687 D-GB-I-E-P
1 l Can plastic	9704 D-GB-F-ARAB
1 l Can plastic	20032 GB-F-E-USA-CAN
1 l Can plastic	2381 D-RUS-UA
1 l Can plastic	20461 D-PL-H-RO-TR
5 l Canister plastic	20662 D-GB-I-E-P
5 l Canister plastic	39020 D-RUS-UA
20 l Canister plastic	3688 D-GB-I-E-P
20 l Canister plastic	20034 GB-F-E-USA-CAN
60 l Drum sheet metal	3689 D-GB
205 l Drum sheet metal	20624 D-GB

# Product information

PI 40/30/01/2018



## Top Tec ATF 1800

**Our information is based on thorough research and may be considered reliable, although not legally binding.**