

## A/C System Cleaner

### Description

Cleaning fluid for removing mold and bacteria (e.g. legionella) simply and effectively from A/C systems in passenger cars, commercial vehicles, buses and in the home without dismantling. Leaves behind a pleasantly fresh fragrance after cleaning. **Use biocides safely. Always read the label and product information before use.**

### Properties

- destroys molds and bacteria
- cleans air inlet ducts
- removes musty smells
- assures fresh, clean air
- forms a protective film
- increases ride comfort
- expert's microbiological report available

### Technical data

Base	Desinfektionsmittel, Geruchshemmer, Duftstoffe / disinfectant, odour remover, fragrances
Color / appearance	farblos / colourless
Density at 20 °C	1,0 g/ml
Odor	Zitrone / lemon
Form	flüssig / liquid
Shelf life	24 Monate in original verschlossenen Gebinden / 24 months in original sealed containers
Solvent content	0 %
pH value	7
Shelf life in original sealed container	24 months

### Areas of application

Used for cleaning and disinfecting air conditioning systems in passenger motor vehicles and commercial vehicles. The product can also be used for domestic air conditioning systems.

### Application

#### Packed in portions:

1 l will treat one vehicle or one air conditioning system. If the manufacturer of the air conditioning system provides a cleaning service recommendation, this recommendation must be observed. If no model-specific instructions are available from the passenger car manufacturer, follow the LIQUI MOLY recommenda-



tion for application. If possible, spray the cleaning fluid directly onto the surface of the evaporator of commercial vehicle, bus and home A/C systems.

#### LIQUI MOLY recommended use:

- Keep the window open during the cleaning process. Avoid inhaling the vapors during cleaning.
- Check to make sure that the condensation water drainage openings are not blocked.
- Dry the surface of the evaporator for 10 minutes with the engine running using the following heater and blower settings: Switch off the air conditioning unit and set to air circulation. Set the air distribution switch to footwell. Turn the temperature regulator and blower selector to maximum.

#### Cleaning the air conditioning system:

- Insert the probe of the cleaner gun toward the evaporator (center of the vehicle) (see vehicle-specific instructions at [www.liqui-moly.biz](http://www.liqui-moly.biz)).
- Actuate the cleaner gun and move the spray probe carefully back and forth to flush out and clean the evaporator thoroughly.
- Allow 15 - 20 minutes for the cleaning fluid to take effect.
- Dry the surface of the evaporator for 10 minutes with the heater and blower at the same setting as prior to cleaning.
- Replace the dust and pollen filter.

Note: Any cleaner which is spilled must be wiped up using a damp cloth and water.

### Available pack sizes

1 l Canister plastic	4091
	D-GB-F-I-E-P
5 l Canister plastic	4092
	D-GB-F-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**