#### Phone Fax: e-mai

#### Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

#### Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de

# **Product information**Pro-Line Diesel System Cleaner

## Description

Highly effective additive combination for quick, economical cleaning of troublesome deposits in the fuel system of diesel engines. Guarantees optimum corrosion protection and increases the ignition performance.

## **Properties**

- removes deposits from entire fuel system
- guarantees optimum combustion
- saves fuel and reduces pollutant emissions
- cleans the fuel system
- rapid and simple problem-solving
- reduces smoke opacity
- minimizes wear
- good corrosion protection
- highly economical
- optimal engine performance
- improved ignition
- increases operational reliability
- eliminates diesel knocking

# **Technical data**

Base	Additive, Trägerflüssigkeit / additive, carrier fluid
Color / appearance	hellbraun, klar / light brown, clear
Density at 15 °C	0,869 g/cm³
Flash point	63 °C
Viscosity at 40 °C	< 7,0 mm²/s
Odor	charakteristisch / characteristic
Form	flüssig / liquid

### **Areas of application**

For all diesel vehicles, including with common rail and pumped jet injection.

## Application

To be added directly into the fuel tank. For preventive use during every inspection, after repairs to the fuel system, for treating problems or after every JetClean cleaning. To eliminate problems, we recommend mixing the product with the fuel during refueling over approximately 2,000 km. Contents are sufficient for max. 70 l of fuel.

Available pack sizes	
500 ml Can sheet metal	5156 D-GB-I-E-P
500 ml Can sheet metal	1797 D-NL-F-GR-ARAB
500 ml Can sheet metal	2996 GB-DK-FIN-N-S
500 ml Can sheet metal	20811 D-GB-SLO-SRB-HR
500 ml Can sheet metal	20450 D-PL-BG
500 ml Can sheet metal	20918 JP
60 l Drum sheet metal	5159 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.



