# **Product information**

## Pro-Line Radiator Cleaner



## **Description**

A concentrated solution developed specifically for all kinds of cooling systems. Dissolves contaminants containing lime and oil in radiators, heating systems, pipes and in engines. Modern formula containing complexants with active cleaning agents.

### **Properties**

- compatible with antifreezes
- good material compatibility
- neutralizes acids
- disperses sludge
- chemical conversion of lime
- neutral behavior in contact with rubber and plastics
- does not contain acids or alkalis
- removes oil and grease-based contaminants

#### **Technical data**

Form flüssig / liquid

Color / appearance hellgelb / light yellow

Hazard class as per Ger- keine / none

man VbF

pH value ~8,7

Solubility in water mischbar / mixable
Odor charakteristisch /

characteristic

Density at 20 °C 1,029 g/cm<sup>3</sup>

#### Areas of application

Suitable for all water cooling systems in motor vehicles, buses, commercial vehicles, and industrial applications.

#### **Application**

Add contents to the cooling water. Run the heating system. Depending on the degree of contamination let the engine run approximately 10 to 30 minutes. Drain the cleaner and flush out the cooling system with water. Fill the cooling system according to the manufacturer's instructions. Contents will treat up to 50 liters of coolant.



## Available pack sizes

1 l Can sheet metal 5189

D-GB-I-E-P

1 l Can sheet metal 20455

D-PL-BG

Our information is based on thorough research and may be considered reliable, although not legally binding.