

Product information

Pro-Line Engine Wear Protection

PI 15/09/01/2018



Description

Colloidal solid lubricant suspension based on molybdenum disulfide (MoS₂) in mineral oil. The product forms a high-load lubricating film on all rubbing and sliding surfaces. This in turn reduces friction, providing for smoother operation of assemblies and greater engine economy. Tested for turbochargers and catalytic converters.

Properties

- mixable with all commercially available motor oils
- compatible with fine filters
- no deposits
- high thermal stability
- reduces running-in and operating wear
- reduces oil and fuel consumption
- increases smooth operation
- outstanding emergency-running properties

Technical data

Base	MoS ₂ -Mineralöl / MoS ₂ mineral oil
Color / appearance	schwarz / black
Density at 20 °C	0,903 g/ml DIN 51757
Particle fineness of MoS ₂	0,3 µm
Viscosity at 40 °C	95 mPas
Flash point	201 °C

Areas of application

Added to lubricating oil of gasoline and diesel engines in passenger cars, commercial vehicles, buses, agricultural vehicles, construction machinery, compressors and pumps. Mixable with all commercially available motor oils.

Application

Contents sufficient to treat up to 25 liters of motor oil. The product can be added to the motor oil at any time.

Note: Do not use in vehicle systems equipped with a wet clutch!



Available pack sizes

1 l Can sheet metal	5197
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.