

AERO RainAway

Description

Special rain repellent for the aviation sector for optimum visibility even at low speeds. Repels water even before taxiing, thereby providing clear visibility while the aircraft is still taxiing. The treated surface reduces adherence, making it easier for insects to be removed.

Properties

- assures a clear view and safety
- suitable for polycarbonate
- Tested for UV at altitude

Technical data

Base	wasserabweisende Wirkstoffkombination / a combination of water repellent agents
Color / appearance	farblos / colourless
Form	flüssig / liquid
Density	0,794 g/cm ³ DIN 51757
Viscosity at 40 °C	< 7 mm ² /s DIN 51562
Flash point	12 °C DIN ISO 2592
pH value	n.a
Solubility	nicht bestimmt
Odor	alkoholisch / alcoholic
Water soluble	mischbar / mixable

Areas of application

Compatible with polycarbonate and therefore suitable for all windshields in the aviation sector. Provides safe and clear visibility while the aircraft is still taxiing or on a landing approach at low propeller rpms. Specially formulated for the needs of general aviation.

Application

Clean and dry the windshield thoroughly. Pour the product on a clean cloth and apply under pressure with circular motions. After approximately 10 minutes, polish with a cloth until the windshield is clear. It is advisable to apply the product every four weeks.



Available pack sizes

125 ml Can aerosol	5904
	D-GB-F

Our information is based on thorough research and may be considered reliable, although not legally binding.