

Cable Grease

Description

High quality lubricant for the lubrication and preservation of wire cables. Excellent corrosion protection enables the use of the product for cavity sealing and underfloor protection in the automotive sector.

Properties

- outstanding corrosion protection
- low aromatic
- highest load-carrying capacity
- high bond strength
- optimum effectiveness when the product is used unmixed
- excellent creep properties
- repels moisture
- has a lasting effect

Technical data

Shelf life	24 Monate bei +10°C bis +30°C (frostfrei) / 24 months at +10°C to +30°C (frost-free)
Run time at 25 °C	30 +/- 4 s
Density at 15 °C	0,85 g/cm ³
Solids content	55 %
Base	Mineralöle, Wachse, Polymere / Mineral oils, wax, polymers
Color / appearance	braun / brown
Flash point	> 60 °C
Dropping point	> 75 °C
Viscosity at 40 °C	20,5 mm ² /s
Odor	charakteristisch / characteristic
Form	flüssig, viskos / liquid, viscous
Shelf life in original sealed container	30 months

Areas of application

For the preventive lubrication, relubrication and preservation of wire cables. Ideally suited for the cavity sealing and underfloor protection of vehicles.

Application

Application is by means of the cavity pistol (part no. 6226) and the cavity probe (part no. 6208). An adherent film is formed after the solvent evaporates. Pay attention to the relevant manufacturer's instructions.



Comment

Shake small packaging before using. Stir big packaging before using.

Available pack sizes

1 l Can sheet metal	6173 D-GB-I-E-P
5 l Can sheet metal	6124 D-GB-I-E-P
25 l Bucket sheet metal	6174 D
60 l Drum sheet metal	6175 D

Our information is based on thorough research and may be considered reliable, although not legally binding.