

# Product information

## Pro-Line Tacky Lube Spray

PI 23/23/11/2017



### Description

High-grade synthetic, heat-resistant lubricant compound that is extremely adherent and resistant to acceleration forces. The solvent evaporates to leave behind an extremely adherent film of grease. The special formulation ensures optimum corrosion protection and impressive sealing properties. The high pressure absorbency and long-lasting effect mean all components have optimum protection even under extreme conditions.

### Properties

- highest load-carrying capacity
- very good resistance to cold and hot water
- outstanding corrosion protection
- outstanding bond strength
- outstanding thermal stability
- optimum effectiveness when the product is used unmixed
- excellent creep properties
- also suitable for overhead work
- has a lasting effect
- clean application

### Technical data

|                                |   |
|--------------------------------|---|
| Base                           | Syntheseöl,<br>Polymergemisch /<br>synthetic oil, mixed<br>polymers |
| Color / appearance             | hellgelb / pale yellow  |
| Operating temperature<br>range | -30 bis / to +180,<br>kurzfristig bis /<br>intermittent to +200 °C  |
| Propellant                     | Propan, Butan / propane,<br>butane                                  |

Shelf life in original sealed container 60 Monate

### Areas of application

**Automotive applications:** For preventive periodic lubrication of components in the automotive and industrial sector, such as hinges, joints, linkages, relay levers, spindles, guides, slide rails, door bolts, bearings and spring balancers.

**Industrial applications:** Spraying over large areas allows a highly adherent corrosion protection to be produced on stationary steel surfaces. For new and periodic lubrication of components in the industrial sector, such as slide rails, hinges, joints, linkages, relay levers, spindles, guides and bearings.



### Application

The surfaces to be treated must be clean and free from residues such as dirt and moisture. Shake well before use. Depending on application, spray on a coating of the desired thickness. The fold-out capillary tube ensures precision spraying. If the capillary tube is left folded in, large areas can be sprayed. Spray large areas without the capillary tube from about 20-25 cm. Overhead spraying also possible.

### Available pack sizes

|                    |                        |
|--------------------|------------------------|
| 400 ml Can aerosol | 7388<br>D-GB-I-E-P     |
| 400 ml Can aerosol | 9915<br>GB-DK-FIN-N-S  |
| 400 ml Can aerosol | 20676<br>D-NL-F-GR-RUS |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**