

## Cold Spray

### Description

Universal application for repair purposes and locating faults. Helps to insert structural components in extremely tight spaces, locate faults in electrical circuits caused by thermal overloading and quickly and easily check the function of temperature sensors. Tissue samples can also be prepared for microscopic analysis in the medical sector.



### Properties

- universal application
- does not contain flammable solvents
- risk of freezing upon contact with the skin
- rapid localized cooling

### Technical data

Color / appearance	farblos / colourless
Base	spezielles Kältemittel / special cryogen
Propellant	Propan, Butan / propane, butane
Density	0,56 g/ml
Flash point	-60 °C
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic

### Available pack sizes

400 ml Can aerosol	8916
	D-GB-NL-F
400 ml Can aerosol	2826
	GB-DK-FIN-N-S

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Areas of application

For inserting ball bearings, shafts and bushings in spaces, for locating faults on electrical components caused by thermal overloading and for the functional check of temperature sensors. Also for cooling down hot parts and for preparing tissue samples for microscopic analysis.

### Application

Evenly spray components or objects to be treated for a few seconds. The freezing effect can be varied according to the duration of spraying. Harmless if used properly. There is a risk of freezing on contact with the body.