

Motorbike Foam Filter Oil (Spray)

Description

Motorbike Air Filter Oil is a specially developed product for wetting foam and fabric air filters. Dust and dirt are reliably deterred even under extreme operating conditions and engine damage is thus avoided. Motorbike Air Filter Oil guarantees an optimum air flow and thereby maximum engine performance.

Properties

- waterproof
- binds dust and sand
- improves filter properties
- long engine service life
- reduces wear
- extremely adherent

Technical data

| | |
|--------------------|------------------------------------|
| Density | 0,676 g/ml g/cm ³ |
| Base | Polymere / polymers |
| Form | flüssig, aerosol / liquid, aerosol |
| Odor | charakteristisch / characteristic |
| Flash point | -60 °C |
| Color / appearance | blau / blue |

Areas of application

Motorbike Air Filter Oil is suitable for use on all two-stroke and four-stroke motorbikes as well as vehicles with air or water-cooled engines using foam or fabric air filters.

Application

First free the filter of coarse contaminants by knocking them out. Clean air filter with Liqui Moly Cleaner and Thinner, part no. 6130, and moisten with Motorbike Air Filter Oil after the solvents have evaporated. Before installing the air filter, allow it to air out for 10 to 15 minutes.

When working with Motorbike Air Filter Oil, make sure that the area is well ventilated.



Available pack sizes

| | |
|--------------------|------------------------|
| 400 ml Can aerosol | 1604 D-GB-I-E-P |
| 400 ml Can aerosol | 5933 D-F-I-GR |
| 400 ml Can aerosol | 20745 GB-DK-FIN-N-S |

Our information is based on thorough research and may be considered reliable, although not legally binding.